

Express Mail No. EL844346400US

PATENT APPLICATION OF
YING CHOY SIEW AND THING SIONG LOO
ENTITLED
TEST FIXTURE ASSEMBLY FOR PRINTED CIRCUIT
BOARDS

00925035.0300001

Docket No. S01.12-0801/STL 10011

TEST FIXTURE ASSEMBLY FOR PRINTED CIRCUIT BOARDS

CROSS-REFERENCE TO RELATED APPLICATION

The present application claims priority to Provisional Application Serial
5 No. 60/255,262 filed December 11, 2000 and entitled "PNUEMATIC
ACTUATED CLAMP SYSTEM."

FIELD OF THE INVENTION

The present invention relates generally to a test apparatus and associated
method for circuit boards and more, particularly, but not by limitation to a
10 circuit board test apparatus and method adaptably interfacing to different circuit
board configurations.

BACKGROUND OF THE INVENTION

Circuit board operation is tested prior to assembly of circuit boards in
various products to verify operational integrity of the circuit board components.
15 For test operations, an electrical connection or interface is made between the
circuit components of the circuit board and test equipment or a test engine. The
electrical connection or interface between the test equipment and the circuit
board is established through a test fixture. The test fixture includes first and
second interfaces including a plurality of terminals and the test fixture includes a
20 plurality of leads electrically connecting the plurality of terminals on the first
interface to the plurality of terminals on the second interface. For test
operations, terminals on the first interface electrically couple to terminals or
probes on the test equipment and terminals on the second interface electrically
couple to terminals of a circuit board under test.

25 Different circuit board designs have different terminal or electrical
configurations and thus different test fixtures with different terminal or electrical
configurations are used to test different circuit board configurations. Test
fixtures are removably coupled to the test equipment to install different test
fixtures depending upon the circuit board configuration under test. For accurate
30 test operations, terminals on the first interface of the test fixture must be

09925085-00001

accurately aligned with terminals or probes of the test equipment and terminals on the second interface must be accurately aligned with terminals on the circuit board under test to assure proper electrical connection between the test equipment or assembly and the circuit board. The process of aligning and assembling the test fixture relative to the test assembly can be time consuming and alignment can be difficult slowing test operations. Embodiments of the present invention address this and other problems and provides advantages and features not recognized nor appreciated by the prior art.

SUMMARY OF THE INVENTION

The present invention relates generally to a test system for testing operation of a circuit board. The test system includes a fixture for providing an electrical interface between a test engine or device and a particular circuit board. The test fixture is selectively clamped and/or loaded onto an actuator which moves the fixture from a first position spaced from the test device to a second position where the test fixture is electrically connected with circuitry of the test device for installation. These and various other features as well as advantages which characterize embodiments of the present invention will be apparent upon reading the following detailed description and review of the associated drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic illustration of a test system for printed circuit boards.

FIG. 2 is an exploded illustration of a test assembly for coupling terminals on a printed circuit board to a test engine or test equipment.

FIGS. 3-1 through 3-4 are schematic illustrations of an embodiment of a test system in accordance with an embodiment of the present invention progressively illustrating installation of a test fixture relative to a test engine or equipment for testing operations.

FIGS. 4-3 and 4-4 schematically illustrate the embodiment of the clamp shown in FIGS. 4-1 and 4-2 in a clamped position or orientation for installation of the test fixture.

FIG. 6 is a flow chart illustrating operating steps for testing a printed
10 circuit board.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

FIG. 1 is a schematic illustration of a test system 100 for a printed circuit board 102. As shown, the test system 100 includes a test engine or device 104 illustrated schematically which electrically interfaces with the circuit board 102 for test operations through a test fixture 110. In the illustrated embodiment shown in FIG. 1, the system includes a cover 112 which is electrically coupled to the test engine 104 and electrically interfaces with the circuit board 102 for test operations. A particular circuit board 102 under test is positioned relative to the fixture 110 and the cover 112 to electrically couple to the test engine 104 through terminals on the fixture 110 and cover 112 and preset terminals or probes 114 on the test engine 104.

In the fixture embodiment shown, fixture 110 includes a first interface surface 116 including a plurality of terminals 118 and a second interface surface 120 also including a plurality of terminals 122. As shown in FIG. 1, the first and second interface surfaces 116, 120 are orientated in opposed directions. The fixture 110 is installed as illustrated by line 126 relative to test engine 104 so that terminals 118 on interface surface 116 operably couple to selected terminals or probes 114 on the test engine 104. For test operations, terminals 122 on interface surface 120 couple to terminals 124 on the circuit board 102 under test.

Terminals 118 are electrically coupled to terminals 122 as illustrated schematically by lines 128 to provide an electrical interface or connection between the circuit board 102 under test and the test equipment or test engine 104.

5 In the illustrated embodiment cover 112 includes a plurality of terminals 130. For a test cycle, cover 112 is lowered or moved towards fixture 110 as illustrated by arrow 132 so that terminals 124 on the circuit board 102 electrically couple to the test engine 104 through terminals 130 on cover 112. For test operations, test engine 104 provides a test voltage or current to test
10 operation of the circuit board 102. As previously described different circuit boards have different configurations and terminal arrangements. Thus different fixtures are installed for test operations depending upon the design of the circuit board being tested.

FIG. 2 illustrates an assembly arrangement for installing a particular
15 fixture to electrically couple a circuit board 102 being tested to the test engine 104. In the embodiment shown in FIG. 2, fixture 110 is assembled relative to an adapter plate 140 coupled to the test engine or device 104 by vacuum pressure supplied through a vacuum port 142. As shown, vacuum pressure is supplied through vacuum port 142 so that the fixture 110 is biased toward terminals (not
20 shown) on the adapter plate 140 to provide an electrical connection between the circuit board 102 and the test engine 104. Maintaining proper alignment of the fixture interface can be difficult if there is not proper air sealing between the components or there is warpage of the components of the system. Alignment difficulties can slow testing operation and reduce testing reliability

25 Embodiments of the present invention relates to a test system including an installation assembly to selectively install a particular fixture for test operations. FIGS. 3-1 through 3-4 schematically illustrate an embodiment of a test assembly to install different fixtures relative to test engine 104 for testing different printed circuit boards, where like numbers are used to refer to like parts

09925005-09904

in the previous FIGS. As shown in FIGS. 3-1 through 3-4, the assembly includes a clamp assembly 144 and an actuator 146 to install a clamped fixture 110 relative to the test engine 104 for installation of different fixtures for different circuit board configurations.

5 As shown in FIGS. 3-1 and 3-2, clamp assembly 144 is coupled to actuator 146 and movable thereby so that fixture 110-1 is clamped relative to the actuator 146 and so that actuator 146 moves fixture 110-1 as illustrated by arrow 150 between an extended or raised position shown in FIG. 3-1 and an installed position shown in FIG. 3-2 to install the fixture for test operations. In the
10 extended or raised position shown in FIG. 3-1, the fixture 110-1 is spaced from the test engine 104 and in the installed position shown in FIG. 3-2, the fixture is lowered towards the test engine 104 to electrically couple the fixture 110-1 to the test engine 104.

In the embodiment shown, a pneumatic piston-cylinder actuator is used
15 to move the fixture 110-1 between the extended or raised position and the installed position to install a particular fixture for test operations. Guide pins 160 on the adapter plate 140 insert into guide holes 162 on the fixture 110-1 to align the fixture 110-1 for installation. Although a pneumatic piston cylinder is described, application is not so limited and alternate actuator systems can be
20 employed to move the supported fixture between the raised position and installed position.

FIGS. 3-3 and 3-4 illustrate an operating sequence embodiment for testing a circuit board through the fixture interface. As shown in FIG. 3-3, the circuit board 102 is aligned relative to the fixture 110-1. In the embodiment
25 shown, a cover 112-1 is moved towards fixture 110-1 via actuator 164 as progressively illustrated in FIGS. 3-3 and 3-4. Cover 112-1 is lowered towards fixture 110-1 so that guide pins 166-1, 166-2 on cover 112-1 extend into guide holes 168-1, 168-2 on the fixture 110-1 to align the cover 112-1 relative to the fixture 110-1 for accurate interface connection.

Cover 112-1 also includes guide pins 166-3, 166-4 which extend through holes on the circuit board 102 and fixture 110-1 as illustrated in FIG. 3-4 to align the circuit board 102 to be tested with the fixture base 110-1 and cover 112-1. Also, as shown, fixture 110-1 includes guide pin 169 for insertion
5 through circuit 102 to align the circuit board 102 relative to the test fixture 110-1. Thus, as shown progressively illustrated in FIGS. 3-3 and 3-4, actuator 164 lowers cover 112-1 to bias the circuit board 102 being tested toward fixture 110-1 and to electrically couple terminals on the circuit board 102 to the fixture terminals and cover for electrical interface with the test circuitry of the test
10 engine 104.

In the illustrated embodiment of FIGS. 3-1 through 3-4, fixture 110-1 includes a test board 170 including a plurality of test terminals (not shown) to form the first interface 116 to couple the fixture 110-1 to terminals or probes of the test engine 104. A plurality of probes or pins (not shown) are coupled to the
15 test board 170 to provide an electrical interface between terminals on the test board 170 and terminals 122 on the second interface 120 formed by a tip portion of the pins or probes. Although a particular fixture circuit structure has been described, it should be understood that application of embodiments of the present invention is not limited to the fixture structure embodiment described.

FIGS. 4-1 through 4-4 illustrate an embodiment of a clamp assembly
20 144-1 to install fixture 110-1 relative to the test engine 104 where the fixture 110-1 is loaded, clamped and installed relative to the test engine for test operations. As shown, clamp assembly 144-1 includes first and second clamp members 172, 174 supported in spaced relation. Clamp member 174 includes an enlarged head 176 to form a support surface to load fixture 110-1 for assembly
25 by actuator 146 as shown in FIGS. 4-1 and 4-2. Clamp member 172 includes a head 178 having an elongated dimension 180 and a narrowed dimension 182 as shown in FIG. 4-2. Fixture 110-1 includes a clamp opening 184 also shaped with an elongated length dimension and a narrowed dimension so that the head

09595085-000001

To clamp the fixture for installation, a clamp rotator 186 rotates the clamp member 172 from a first orientation where the elongated length 180 is aligned with the elongated length dimension of clamp opening 184 as shown in FIGS. 4-1 and 4-2 to a second orientation shown in FIGS. 4-3 and 4-4. In the second orientation, the elongated length 180 of the clamp member 172 is aligned with the narrowed dimension of clamp opening 184. The clamp members 172, 174 are spaced relative a thickness of a ledge 188 portion of the fixture 110-1 having the clamp opening 184 so that in the second orientation, the elongated length 180 of clamp member 172 abuts a surface 190 of fixture 110-1 while surface 192 of fixture 110-1 is supported on enlarge head 176 of clamp member 174 to secure fixture 110-1 therebetween. Thereafter, actuator 144 moves clamp members 172, 174 (with the fixture 110-1 secured therebetween) toward the test engine 104 as shown in FIG. 3-2 to install the fixture. Thus, as described, fixture 110-1 can be easily loaded for test operations without extensive installation delay. Although a particular clamp structure is illustrated in FIGS. 4-1 through 4-4 for loading and clamping the fixture for installation, application is not limited to the particular structure shown.

Subsequent to use for a particular circuit board, the test fixture 110-1 is
25 unloaded. The test fixture 110-1 is unloaded by extending actuator 146 to bias
head or support surface 176 against fixture 110-1 to raise fixture 110-1.
Thereafter, rotator 186 rotates clamp member 172 to unclamp the fixture 110-1
and the fixture 110-1 is removed to install a different test fixture if desired. FIG.
5 is a perspective illustration of an embodiment of a test fixture 110-1. As

5

10

25

It is to be understood that even though numerous characteristics and advantages of various embodiments of the invention have been set forth in the

5

10

	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---